

Product Information

Duo - Pellets Conveyor ZSF 151 / 251

Application Area

The conveyors of the **ZSF 151** models are used to convey all kinds of plastics pellets. The products are equipped with a side canal compressor and are used for the automatic filling of **two** plastics processing machines. The GERCO pellets conveyors have special pick-up elements to connect the conveyor machine and the dryer. They have a maximum conveying capacity of 150 kg/h. By attaching the add-on assembly group **Two Components Switch ZKW 22**, an extended application of the conveying unit is possible.



Separator

Control desk

Separator

Standard Features:

- 2 x Stainless steel material precipitator container
- Fan and control unit (side canal compressor), with electronic control are built in (can also be delivered as a positionable control unit)
- Conveying time and conveying cycle can be adjusted separately
- 2 x Suction lance $\varnothing 40$
- 4 x 3 m Delivery hose and return air hose made off PU

Information: So that a flawless function of the conveyor unity can be guaranteed, the material suction management and vacuum management should be with piping.

Product Information


Technical Data

Mechanical Data

ZSF 151

Dimensions (ø x H) in mm hopper	250 x 650
Weight in kg	2 x 8 kg (container)
Conveying performance in kg / h	150
Conveying height in m	4
Conveying length in m	15
Capacity in Liter	8
Noise level 1m distance dB	73

Hopper flange



Electrical Data

Connected load	3 x 400 V, 50 Hz
Fan performance in kW	1.5

The conveying control is painted in light grey RAL 7004.
 On demand you can select another color for an additional charge.
 On demand the connected load can be changed for an additional charge.

Duo - Pellets Conveyor ZSF 151

Accessories

Two components Switch ZKW 22

to convey two materials in the VSF 151, VSF 251, ZSF 151

Flashlight

Adapter container

To mount the conveying units on the machine